

Southwire™

# CABLE TIES

CATALOG

**[ BUILT FOR DURABILITY.  
BUILT FOR RELIABILITY.  
BUILT FOR WORK.™ ]**

SOUTHWIRE.COM

# CABLE TIES

NATURAL WHITE - INDOOR USE



## FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- UL flame rating 94V-2

## APPLICATIONS

- Safely and easily secures wire bundles and harness components

## STANDARD MATERIAL

- 6/6 Nylon

## CERTIFICATIONS

- AH2 Rated
- 50 & 120LB Series UL Type 21S

PART #	LENGTH	TENSILE STRENGTH (LBS.)	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	PACK	CASE QTY.
BL4M9-M	4.1"	18	0.096"	0.035"	.75"	1,000	10,000
BL4M9-C	4.1"	18	0.096"	0.035"	.75"	100	10,000
BL5I9-M	5.7"	40	.142"	0.05"	1.25"	1,000	10,000
BL5I9-C	5.7"	40	.142"	0.05"	1.25"	100	10,000
BL8I9-M	8.7"	40	.142"	0.05"	2"	1,000	10,000
BL8I9-C	8.7"	40	.142"	0.05"	2"	100	10,000
BL7S9-M	7.6"	50	.18"	.054"	2"	1,000	10,000
BL7S9-C	7.6"	50	.18"	.054"	2"	100	10,000
BL11S9-M	11.1"	50	.18"	.054"	3"	1,000	5,000
BL11S9-C	11.1"	50	.18"	.054"	3"	100	5,000
BL14S9-M	14.6"	50	.18"	.054"	4"	1,000	5,000
BL14S9-C	14.6"	50	.18"	.054"	4"	100	5,000
BL8L9-C	9"	120	.298"	.069"	2"	100	2,500
BL11L9-C	12"	120	.298"	.069"	3"	100	2,000
BL11L9-L	12"	120	.298"	.069"	3"	50	2,000
BL14L9-C	14"	120	.298"	.069"	4"	100	2,000
BL14L9-L	14"	120	.298"	.069"	4"	50	2,000
BL24H9-L	24"	175	.350"	.087"	7.20"	50	500
BL36H9-L	36"	175	.350"	.087"	11"	50	500
BL48H9-L	48"	175	.350"	.087"	15"	50	500

BL6X-X (6.1") and BL8X-X (8.1") Series are special order and subject to availability and min order quantities.

CABLE TIES

# CABLE TIES

## BLACK UV STABILIZED INDOOR/OUTDOOR



### FEATURES

- Operating temperature minimum -40°F to maximum 185°F
- UV resistant
- UL flame rating 94V-2

### APPLICATIONS

- Safely and easily secures wire bundles and harness components

### STANDARD MATERIAL

- 6/6 Nylon

### CERTIFICATIONS

- AH2 Rated
- 50 & 120LB Series UL Type 21S

PART #	LENGTH	TENSILE STRENGTH (LBS.)	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	PACK	CASE QTY.
BL4M0-M	4.1"	18	0.096"	0.035"	.75"	1,000	10,000
BL4M0-C	4.1"	18	0.096"	0.035"	.75"	100	10,000
BL5I0-M	5.7"	40	.142"	0.05"	1.25"	1,000	10,000
BL5I0-C	5.7"	40	.142"	0.05"	1.25"	100	10,000
BL8I0-M	8.7"	40	.142"	0.05"	2"	1,000	10,000
BL8I0-C	8.7"	40	.142"	0.05"	2"	100	10,000
BL7S0-M	7.6"	50	.18"	.054"	2"	1,000	10,000
BL7S0-C	7.6"	50	.18"	.054"	2"	100	10,000
BL11S0-M	11.1"	50	.18"	.054"	3"	1,000	5,000
BL11S0-C	11.1"	50	.18"	.054"	3"	100	5,000
BL14S0-M	14.6"	50	.18"	.054"	4"	1,000	5,000
BL14S0-C	14.6"	50	.18"	.054"	4"	100	5,000
BL8L0-C	9"	120	.298"	.069"	2"	100	2,500
BL11L0-C	12"	120	.298"	.069"	3"	100	2,000
BL11L0-C	12"	120	.298"	.069"	3"	100	2,000
BL14L0-C	14"	120	.298"	.069"	4"	100	2,000
BL14L0-L	14"	120	.298"	.069"	4"	50	2,000
BL24H0-L	24"	175	.350"	.087"	7.20"	50	500
BL36H0-L	36"	175	.350"	.087"	11"	50	500
BL48H0-L	48"	175	.350"	.087"	15"	50	500

BL6X-X (6.1") and BL8X-X (8.1") Series are special order and subject to availability and min order quantities.

# CABLE TIES

## INDOOR/OUTDOOR - RELEASABLE



### FEATURES

- Easy to use release tab
- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- Smooth surfaces

### APPLICATIONS

- For indoor or outdoor use
- Releasable cable ties are designed for use in general temporarily or permanent applications, while delivering ease of installation, consistent performance, and industry leading reliability.

### STANDARD MATERIAL

- 6/6 Nylon

### CERTIFICATIONS

- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL7SR9-C	50	INDOOR	NATURAL	7.6"	0.180"	.055"	2"	100	5,000	20
BL11SR9-C	50		NATURAL	11.1"	0.180"	.055"	3"	100	5,000	21
BL14SR9-C	50		NATURAL	14.6"	0.180"	.055"	4"	100	5,000	29
BL7SR9-C	50	INDOOR/ OUTDOOR	BLACK	7.6"	0.180"	.055"	2"	100	5,000	20
BL11SR9-C	50		BLACK	11.1"	0.180"	.055"	3"	100	5,000	21
BL14SR9-C	50		BLACK	14.6"	0.180"	.055"	4"	100	5,000	29

# CABLE TIES - HEAT STABILIZED



### FEATURES

- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- Smooth surfaces
- Max. operating temperature of 22°C

### APPLICATIONS

- For outdoor or indoor use
- Heat Stabilized cable ties are utilized in harsh conditions where extreme heat is a concern.

### STANDARD MATERIAL

- UV/heat stabilized nylon 6.6, black

### CERTIFICATIONS

- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL4MHS0-M	18	OUTDOOR/ INDOOR	BLACK, UV, HS	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17
BL5IHS0-M	40			5.8"	0.142"	0.05"	1.25"	1,000	10,000	17
BL7SHS0-M	50			7.6"	0.18"	0.054"	2"	1,000	10,000	30
BL11SHS0-M				11.1"	0.18"	0.054"	3"	1,000	5,000	26
BL14SHS0-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26
BL14LHS0-C	120			15"	0.298"	0.069"	4"	100	2,000	26

# CABLE TIES - COLD WEATHER



## FEATURES

- Extended UV sunlight protection
- Max operating temp -40°F to 185°F (-20°F install temp)

## APPLICATIONS

- Cold weather ties are used in applications where cold and sunlight are factors.

## STANDARD MATERIAL

- UV/weather resistant nylon 6.6, black

## CERTIFICATIONS

- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	BAG QTY.	CASE QTY.
BL7SAW0-C	50	OUTDOOR/ INDOOR	BLACK, UV	7.60"	.18"	.054"	100	10,000
BL11SAW0-C				11.10"	.18"	.054"	100	5,000
BL14SAW0-C				14.60"	.18"	.054"	100	5,000
BL14LAW0-C	120			15"	.298"	.069"	100	2,000

# EZ-OFF™ CABLE TIES



## FEATURES

- Simply pull down tear-off arm located along the right side of cable tie head
- Patent # 7,062,820

## APPLICATIONS

- EZ-OFF™ cable ties are designed specifically to be tamper proof and removed without any cutting device.

- For indoor use

## STANDARD MATERIAL

- Polypropylene

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	CASE QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BLTSP69-M	30	INDOOR	NATURAL	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP60-M			BLACK	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP62-M			RED	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP63-M			ORANGE	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP64-M			YELLOW	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP65-M			GREEN	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP66-M			BLUE	5.60"	0.14"	0.054"	1,000	10,000	23
BLTSP67-M			PURPLE	5.60"	0.14"	0.054"	1,000	10,000	23

# CABLE TIES - COLORED



## FEATURES

- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- Smooth surfaces

## APPLICATIONS

- For indoor use
- Colored cable ties are designed for use in general applications where unique identification is needed, while delivering ease of installation, consistent performance, and industry leading reliability.

## STANDARD MATERIAL

- Nylon 6.6

## CERTIFICATIONS

- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)		
BL4M1-M	18	INDOOR	BROWN	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17		
BL4M1-C				4.1"	0.096"	0.035"	0.75"	100	10,000	17		
BL5I1-M	40			5.8"	0.142"	0.05"	1.50"	1,000	10,000	17		
BL5I1-C				5.8"	0.142"	0.05"	1.50"	100	10,000	17		
BL8I1-M	40			8.9"	0.142"	0.05"	2"	1,000	10,000	24		
BL8I1-C				8.9"	0.142"	0.05"	2"	100	10,000	24		
BL7S1-M	50			7.6"	0.18"	0.054"	2"	1,000	10,000	30		
BL7S1-C				7.6"	0.18"	0.054"	2"	100	10,000	30		
BL11S1-M				11.1"	0.18"	0.054"	3"	1,000	5,000	21		
BL11S1-C				11.1"	0.18"	0.054"	3"	100	5,000	21		
BL14S1-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26		
BL14S1-C				14.6"	0.18"	0.054"	4"	100	5,000	26		
BL4M2-M	18			INDOOR	RED	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17
BL4M2-C						4.1"	0.096"	0.035"	0.75"	100	10,000	17
BL5I2-M	40	5.8"	0.142"			0.05"	1.50"	1,000	10,000	17		
BL5I2-C		5.8"	0.142"			0.05"	1.50"	100	10,000	17		
BL8I2-M	40	8.9"	0.142"			0.05"	2"	1,000	10,000	24		
BL8I2-C		8.9"	0.142"			0.05"	2"	100	10,000	24		
BL7S2-M	50	7.6"	0.18"			0.054"	2"	1,000	10,000	30		
BL7S2-C		7.6"	0.18"			0.054"	2"	100	10,000	30		
BL11S2-M		11.1"	0.18"			0.054"	3"	1,000	5,000	21		
BL11S2-C		11.1"	0.18"			0.054"	3"	100	5,000	21		
BL14S2-M		14.6"	0.18"			0.054"	4"	1,000	5,000	26		
BL14S2-C		14.6"	0.18"			0.054"	4"	100	5,000	26		

CABLE TIES

# CABLE TIES - COLORED CONTINUED

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)		
BL4M3-M	18	INDOOR	ORANGE	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17		
BL4M3-C				4.1"	0.096"	0.035"	0.75"	100	10,000	17		
BL5I3-M	40			5.8"	0.142"	0.05"	1.50"	1,000	10,000	17		
BL5I3-C				5.8"	0.142"	0.05"	1.50"	100	10,000	17		
BL8I3-M				8.9"	0.142"	0.05"	2"	1,000	10,000	24		
BL8I3-C	50			8.9"	0.142"	0.05"	2"	100	10,000	24		
BL7S3-M				7.6"	0.18"	0.054"	2"	1,000	10,000	30		
BL7S3-C				7.6"	0.18"	0.054"	2"	100	10,000	30		
BL11S3-M				11.1"	0.18"	0.054"	3"	1,000	5,000	21		
BL11S3-C				11.1"	0.18"	0.054"	3"	100	5,000	21		
BL14S3-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26		
BL14S3-C	14.6"			0.18"	0.054"	4"	100	5,000	26			
BL4M4-M	18			INDOOR	YELLOW	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17
BL4M4-C						4.1"	0.096"	0.035"	0.75"	100	10,000	17
BL5I4-M	40	5.8"	0.142"			0.05"	1.50"	1,000	10,000	17		
BL5I4-C		5.8"	0.142"			0.05"	1.50"	100	10,000	17		
BL8I4-M		8.9"	0.142"			0.05"	2"	1,000	10,000	24		
BL8I4-C	50	8.9"	0.142"			0.05"	2"	100	10,000	24		
BL7S4-M		7.6"	0.18"			0.054"	2"	1,000	10,000	30		
BL7S4-C		7.6"	0.18"			0.054"	2"	100	10,000	30		
BL11S4-M		11.1"	0.18"			0.054"	3"	1,000	5,000	21		
BL11S4-C		11.1"	0.18"			0.054"	3"	100	5,000	21		
BL14S4-M		14.6"	0.18"			0.054"	4"	1,000	5,000	26		
BL14S4-C	14.6"	0.18"	0.054"			4"	100	5,000	26			
BL4M5-M	18	INDOOR	GREEN			4.1"	0.096"	0.035"	0.75"	1,000	10,000	17
BL4M5-C						4.1"	0.096"	0.035"	0.75"	100	10,000	17
BL5I5-M	40			5.8"	0.142"	0.05"	1.50"	1,000	10,000	17		
BL5I5-C				5.8"	0.142"	0.05"	1.50"	100	10,000	17		
BL8I5-M				8.9"	0.142"	0.05"	2"	1,000	10,000	24		
BL8I5-C	50			8.9"	0.142"	0.05"	2"	100	10,000	24		
BL7S5-M				7.6"	0.18"	0.054"	2"	1,000	10,000	30		
BL7S5-C				7.6"	0.18"	0.054"	2"	100	10,000	30		
BL11S5-M				11.1"	0.18"	0.054"	3"	1,000	5,000	21		
BL11S5-C				11.1"	0.18"	0.054"	3"	100	5,000	21		
BL14S5-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26		
BL14S5-C	14.6"			0.18"	0.054"	4"	100	5,000	26			

CABLE TIES

# CABLE TIES - COLORED CONTINUED

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)	
BL4M6-M	18	INDOOR	BLUE	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17	
BL4M6-C				4.1"	0.096"	0.035"	0.75"	100	10,000	17	
BL5I6-M	40			5.8"	0.142"	0.05"	1.50"	1,000	10,000	17	
BL5I6-C				5.8"	0.142"	0.05"	1.50"	100	10,000	17	
BL8I6-M				8.9"	0.142"	0.05"	2"	1,000	10,000	24	
BL8I6-C				8.9"	0.142"	0.05"	2"	100	10,000	24	
BL7S6-M	50	INDOOR		7.6"	0.18"	0.054"	2"	1,000	10,000	30	
BL7S6-C				7.6"	0.18"	0.054"	2"	100	10,000	30	
BL11S6-M				11.1"	0.18"	0.054"	3"	1,000	5,000	21	
BL11S6-C				11.1"	0.18"	0.054"	3"	100	5,000	21	
BL14S6-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26	
BL14S6-C				14.6"	0.18"	0.054"	4"	100	5,000	26	
BL4M7-M	18		INDOOR	PURPLE	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17
BL4M7-C					4.1"	0.096"	0.035"	0.75"	100	10,000	17
BL5I7-M	40				5.8"	0.142"	0.05"	1.50"	1,000	10,000	17
BL5I7-C					5.8"	0.142"	0.05"	1.50"	100	10,000	17
BL8I7-M					8.9"	0.142"	0.05"	2"	1,000	10,000	24
BL8I7-C					8.9"	0.142"	0.05"	2"	100	10,000	24
BL7S7-M	50	7.6"			0.18"	0.054"	2"	1,000	10,000	30	
BL7S7-C		7.6"			0.18"	0.054"	2"	100	10,000	30	
BL11S7-M		11.1"			0.18"	0.054"	3"	1,000	5,000	21	
BL11S7-C		11.1"			0.18"	0.054"	3"	100	5,000	21	
BL14S7-M		14.6"			0.18"	0.054"	4"	1,000	5,000	26	
BL14S7-C		14.6"			0.18"	0.054"	4"	100	5,000	26	
BL4M8-M	18	INDOOR	GRAY	4.1"	0.096"	0.035"	0.75"	1,000	10,000	17	
BL4M8-C				4.1"	0.096"	0.035"	0.75"	100	10,000	17	
BL5I8-M	40			5.8"	0.142"	0.05"	1.50"	1,000	10,000	17	
BL5I8-C				5.8"	0.142"	0.05"	1.50"	100	10,000	17	
BL8I8-M				8.9"	0.142"	0.05"	2"	1,000	10,000	24	
BL8I8-C				8.9"	0.142"	0.05"	2"	100	10,000	24	
BL7S8-M	50			7.6"	0.18"	0.054"	2"	1,000	10,000	30	
BL7S8-C				7.6"	0.18"	0.054"	2"	100	10,000	30	
BL11S8-M				11.1"	0.18"	0.054"	3"	1,000	5,000	21	
BL11S8-C				11.1"	0.18"	0.054"	3"	100	5,000	21	
BL14S8-M				14.6"	0.18"	0.054"	4"	1,000	5,000	26	
BL14S8-C				14.6"	0.18"	0.054"	4"	100	5,000	26	

CABLE TIES



# CABLE TIES - MOUNTING HEAD



## FEATURES

- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- Smooth surfaces

## APPLICATIONS

- Screw mount cable ties allow cable bundles to be secured permanently to any surface.
- Ideal for communication racks, walls, or ceilings.

## STANDARD MATERIAL

- Indoor: Nylon 6.6, natural
- Outdoor: UV stabilized nylon 6.6, black

## CERTIFICATIONS

- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL7SMH9-C	50	INDOOR	NATURAL	7.60"	0.18"	0.055"	2"	100	5,000	20
BL11SMH9-C	50		NATURAL	11.60"	0.18"	0.055"	3"	100	5,000	21
BL14SMH9-C	50		NATURAL	14.60"	0.18"	0.055"	4"	100	5,000	29
BL14LML9-C	120		NATURAL	15.10"	0.298"	0.069"	4"	100	2,000	31
BL7SMH0-C	50	OUTDOOR/ INDOOR	BLACK, UV	7.60"	0.18"	0.055"	2"	100	5,000	20
BL11SMH0-C	50		BLACK, UV	11.60"	0.18"	0.055"	3"	100	5,000	21
BL14SMH0-C	50		BLACK, UV	14.60"	0.18"	0.055"	4"	100	5,000	29
BL14LMH0-C	120		BLACK, UV	15.10"	0.298"	0.069"	4"	100	2,000	31

\*Length of tie not including mounting head

# CABLE TIES - METAL DETECTABLE



## FEATURES

- Teal color of easy identification in food processing areas
- Easy grab tip for pick up from flat surfaces
- Low insertion for quick installation
- Smooth surfaces

## APPLICATIONS

- Metal Detectable cable ties are impregnated with metal flakes and can be used safely and efficiently in a wide range of indoor food processing applications.

## STANDARD MATERIAL

- Nylon 6.6, teal

## CERTIFICATIONS

- FDA Approved: Complies with 21 CFR 177-1500
- UL Listed

PART #	TENSILE STRENGTH (LBS)	ENVIRONMENT	COLOR	LENGTH	WIDTH	BAG QTY.	CASE QTY.	WEIGHT/ CASE (LBS.)
BL4MMD-C	18	INDOOR	TEAL	4.1"	0.096"	100	10,000	18
BL4MMD-M	18			4.1"	0.096"	1,000	10,000	18
BL8IMD-C	40			8.7"	0.142"	100	10,000	24
BL8IMD-M	40			8.7"	0.142"	1,000	10,000	24
BL7SMD-C	50			7.6"	0.180"	100	10,000	30
BL7SMD-M	50			7.6"	0.180"	1,000	10,000	30
BL11SMD-C	50			11.1"	0.180"	100	5,000	21
BL14SMD-C	50			14.6"	0.180"	100	5,000	26
BL14LMD-C	120			15.0"	0.298"	100	2,500	26

CABLE TIES

# AIR HANDLING CABLE TIES

6/6 NYLON



## FEATURES

- Meets UL 1565 specifications for low smoke generation, low heat release and mechanical strength
- Strong and pure, manufactured from filtered nylon 6/6, reducing particle contamination
- Low profile style and reduced head height increases safety, eliminates snags, cuts, and abrasions to cables, surrounding products and users

## APPLICATIONS


- Air handling spaces, above drop ceilings and below raised flooring
- UL listed suitable for use in air handling spaces in accordance with the section 300.00 (c) and (d) of the National Electrical Code rules 12-010(3), (4) and (5) and 12-020 of the Canadian Electrical Code part 1

## STANDARD MATERIAL

- 6/6 nylon

PART #	TENSILE STRENGTH (LBS)	COLOR	LENGTH	WIDTH	THICKNESS	MAX. BUNDLE DIAMETER	PACK	CASE QTY.
BL4MAH-C	18 LB	BURGUNDY	4.1"	0.096"	0.035"	.75"	100	10,000
BL7SAH-C	50 LB	BURGUNDY	11.1"	.18"	.054"	2"	100	5,000
BL11SAH-C	50 LB	BURGUNDY	14.6"	.18"	.054"	3"	100	5,000
BL14SAH-C	50 LB	BURGUNDY	14.6"	.18"	.054"	4"	100	5,000
BL14LAH-C	120 LB	BURGUNDY	15"	.298"	.069"	4"	100	2,000

# CABLE TIE MOUNTS WITH ADHESIVE



## FEATURES

- Apply with adhesive base or screw
- Available in black or white

## APPLICATIONS

- For safe organization of cables

## STANDARD MATERIAL

- 6/6 nylon

PART #	"ADHESIVE TYPE"	COLOR	LENGTH	WIDTH	THICKNESS	MIN. BUNDLE DIAMETER	SCREW SIZE	INNER QTY.	MASTER QTY.
BLMPM9-C	RUBBER	NATURAL	3/4"	3/4"	.1875"	.165"	0.162"	100	10,000
BLMPM9-L	RUBBER	NATURAL	3/4"	3/4"	.1875"	.165"	0.162"	50	10,000
BLMPM0-C	RUBBER	BLACK	3/4"	3/4"	.1875"	.165"	0.162"	100	10,000
BLMPM0-L	RUBBER	BLACK	3/4"	3/4"	.1875"	.165"	0.162"	50	10,000
BLMPS9-C	RUBBER	NATURAL	1"	1"	.198"	.22"	.210"	100	5,000
BLMPS9-L	RUBBER	NATURAL	1"	1"	.198"	.22"	.210"	50	5,000
BLMPS0-C	RUBBER	BLACK	1"	1"	.198"	.22"	.210"	100	5,000
BLMPS0-L	RUBBER	BLACK	1"	1"	.198"	.22"	.210"	50	5,000
BLMPMA9-C	ACRYLIC	NATURAL	3/4"	3/4"	.1875"	.165"	0.162"	100	10,000
BLMPMA0-C	ACRYLIC	BLACK	3/4"	3/4"	.1875"	.165"	0.162"	100	10,000
BLMPSA9-C	ACRYLIC	NATURAL	1"	1"	.198"	.22"	.210"	100	5,000
BLMPSA0-C	ACRYLIC	BLACK	1"	1"	.198"	.22"	.210"	100	5,000

CABLE TIES



**Southwire™**

# **CABLE TIES**

## **CATALOG**

### **GET SOCIAL WITH US:**



**/SOUTHWIRETOOLS**  
**/SOUTHWIRETOOLSLATINO**



**@SOUTHWIRETOOLS**



**@SOUTHWIRETOOLS**



**SOUTHWIRETOOLS**

**SOUTHWIRE.COM | 1-855-SWTOOLS**

All Trademarks or Registered Trademarks (TM/®) are owned or licensed by Southwire Company.  
Any other TM/® - Trademark or Registered Trademark of Southwire Company.